Tab Table

Designed by Edward Barber and Jay Osgerby

Table and floor lamps providing direct lighting with adjustable head. Bodyin painted pressofused aluminium. Multi-led diffuser in specially designed PMMA to avoid the Multi Shadoweffect and dazzle. Head rotation from ± 90°

Main specifications

Mounting Environment

Light source type Light source replaceable Indoor dry location LED Replaceable (LEDonly)light source by a professional . LED Module

Table

Lamp holder **Autoprotected Lamp** Number of heads Source Power (W) System Flux (Im)

LED Module Νo 347lm

120°

1


9

LED type

Optical

Lighting Type Lighting distribution CCT (K) CRI> **Cold Beam Lighting** Extreme Cut off

Direct Asymmetric 2700 80 No No



2 D 60 300 400 30° 30 0 - C0 / C180 cd / 1000 **I**m C90 / C270

Electrical
Insulation class
Frequency (Hz)
Main Voltage (Vac)
Driver

Dimmable type

ш 50/60 100-240/24 Remote included Electronic 12V

0.91 2.01 20


20

Batteries Inside Power supply replaceable	N o Repla contr
Cord length (mm) Plug Type	an en 1600 Type (
Charging Min Time	Type (N o

aceable rol gear by nd-user G, Type A, С No

Physical	
Net weight (kg)	
Gross weight (kg)	
IP	
IP external	

-		-	
	5		



273 mm

